

GAM835



All wheel position tire designed for on/off road applications. Ideal for heavy haul service such as logging, mining, oil fields, refuse, mixer and or dump trucks.

Features

Benefits

New casing construction with optimized tread profile

- ▶ Provides optimal footprint for improved wear and vehicle handling

Wide solid shoulder

- ▶ Improves protection of the casing and increases stability and comfort for the driver

Advanced cut/chip resistant tread compound

- ▶ High resistance against tread tearing from normal usage on aggressive road surfaces

Combined rib and lug pattern design

- ▶ Delivers excellent traction and braking properties in all positions

SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1494G	16	H	148/145 K	8.25	7.50	6,940@123	6,395@123	11.0	19.3	41.5	24	501	132
315/80R22.5	100EV1182G	22	M	161/157 J	9.00	9.75	10,200@130	9,090@130	12.3	19.7	42.4	24	490	158
11R24.5	100EV889G	16	H	149/146 K	8.25	7.50	7,160@120	6,610@120	11.0	20.3	43.5	24	478	141

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius