

GDL650 FS SmartWay Verified



A versatile drive axle tire designed for long-haul services while providing long tread life and retreadability.

Features

Special compound with low rolling resistance and low heat generation

Big zigzag longitudinal groove design

Transverse zigzag groove & tie bar design

Stone rejector design on groove wall

Solid shoulder rib

Multiple edges of block

Benefits

- ▶ Reduces rolling resistance performance effectively and improves fuel economy
- ▶ Ensures good traction and driving stability
- ▶ Enhances block stiffness and prevents the “heel & toe” problem to achieve longer mileage
- ▶ Protects the belt from stone puncturing
- ▶ Prevents shoulder from irregular wear
- ▶ Promotes excellent traction



SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1428G	14	G	144/142 L	8.25	7.50	6,175@105	5,840@105	11.0	—	41.5	26	501	129
295/75R22.5	100EV1671G	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	—	40.2	26	517	125
11R24.5	100EV409G	14	G	146/143 L	8.25	7.50	6,610@105	6,005@105	11.0	—	43.7	26	475	138
285/75R24.5	100EV1478G	14	G	144/141 L	8.25	—	6,175@110	5,675@110	11.1	—	41.6	26	499	126

PR Ply Rating **LR** Load Range **SR** Speed Rating **SLR** Static Loaded Radius

FS Fuel Saving Specification