

GDR639



Non-directional drive axle pattern designed to deliver exceptional traction and outstanding mileage performance.

Features

Modern open shoulder pattern

Deeper groove depth

Specific shoulder design

Wide footprint with square shoulders

Benefits

- ▶ Excellent traction in a variety of regional applications
- ▶ Extends long life
- ▶ Provides excellent water evacuation and heat dispersion
- ▶ Helps provide enhanced stability



SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1499G	16	H	148/145 L	8.25	7.50	6,940@120	6,395@120	11.0	—	41.5	30	501	138
295/75R22.5	100EV1670G	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	—	40.4	30	514	136
11R24.5	100EV1445G	14	G	146/143 L	8.25	7.50	6,610@105	6,005@105	11.0	—	43.9	30	473	146
11R24.5	100EV1621G	16	H	149/146 L	8.25	7.50	7,160@120	6,610@120	11.0	—	43.9	30	473	148
285/75R24.5	100EV1477G	14	G	144/141 L	8.25	--	6,175@110	5,675@110	11.1	—	41.8	30	497	136

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius