

GT686



Directional deep tread drive axle pattern for mixed service and on/off road applications.

Features

Directional extra deep tread with wide longitudinal grooves

Special anti-cut and chip compound

Big block and widened lug groove

Directional and gradually open lug pattern

Benefits

- ▶ Provides exceptional grip in rough terrain conditions with excellent self cleaning properties
- ▶ Provides excellent protection from tread cuts and damage
- ▶ Better traction performance
- ▶ Better self-clean performance



SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)						Inch
11R22.5	100EV834G	16	H	148/145 J	8.25	7.50	6,940@123	6,395@123	11.0	19.3	41.5	28	501	138
12R22.5	100EV366G	16	H	152/148 K	9.00	8.25	7,830@123	6,940@123	11.8	19.8	42.7	29	487	153
315/80R22.5	100EV546G	18	J	156/150 K	9.00	9.75	8,810@120	7,390@120	12.3	19.7	42.4	29	490	163

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius