



All position three groove tire design for city bus and urban delivery application.

Features

- Sidewall protector
- Solid shoulder design
- Wider tread with deeper grooves
- Reinforced sidewall protector ribs
- Robust casing construction with cap and base technology

Benefits

- ▶ Effectively protects sidewall
- ▶ Enhances cornering stiffness on shoulders
- ▶ Enhances tire life
- ▶ Superior resistance to curbing and impact damage
- ▶ Excellent mileage performance and reduced noise level



SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5*	100EV748G	16	H	148/145 J	8.25	7.50	6,940@120	6,395@120	11.0	19.3	41.5	24	501	134
275/70R22.5	100EV774G	16	H	148/145 J	9.00	8.25	6,945@130	6,395@130	10.9	17.5	37.7	24	551	127
295/80R22.5	100EV375G	16	H	152/148 J	8.25	9.00	7,830@123	6,940@123	11.7	19.2	41.3	24	503	151

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius

*SmartWay Verified. Giti Tire Manufactures SmartWay Verified Technologies. Learn more at epa.gov/smartway.