

# GT876



Designed for heavy axles, this all wheel position wide base radial provides exceptional service in on/off highway and heavy haul applications.

## Features

Aggressive tread pattern

Special cut and chip compound

Deep tread depth

Wide foot print

Robust casing

## Benefits

- ▶ Superior traction in soft and hard roads
- ▶ High resistance to cutting and tearing
- ▶ Extended tread life
- ▶ Maximum flotation
- ▶ Exceptional durability and retreadability



## SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
385/65R22.5	100EV556G	18	J	158/- L (160/-) (K)	11.75	12.25	9,370@123 (9,920@130)	—	15.3	19.5	42.2	23	492	170
425/65R22.5	100EV850G	20	L	165/- K	12.25	11.75 13.00	11,400@120	—	16.6	20.4	44.3	23	469	204
445/65R22.5	100EV840G	20	L	169/- K	13.00	12.25 14.00	12,800@130	—	17.5	20.8	45.3	23	459	223

PR Ply Rating    LR Load Range    SR Speed Rating    SLR Static Loaded Radius