

GT978+



Perfectly suited for regional and mixed service steer, this all position radial delivers exceptional mileage performance and durability.

Features

Five zigzag rib pattern

Special cut and chip compound

Shoulder reinforcement design

Wide deep tread

Robust casing

Benefits

- ▶ Excellent traction and stability
- ▶ High resistance to cutting and tearing
- ▶ Enhanced casing protection design
- ▶ Optimum wear performance
- ▶ Exceptional durability and retreadability

SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
385/65R22.5	100EV559G	18	J	158/- L (160/-) (K)	11.75	12.25	9,370@123 (9,920@130)	-	15.3	19.5	42.2	20	492	168
425/65R22.5	100EV851G	20	L	165/-K	12.25	13.00	11,400@120	-	16.9	20.4	44.3	20	469	204

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius