

GT988+



New generation of high performance drive axle tires for medium sized trucks.

Features

Five circumferential groove design

Circumferential groove and specific tread design

Specific tread compound

Benefits

- ▶ Equate tread pressure and abrasion
- ▶ Helps lower rolling resistance and saves energy
- ▶ Low heat generation and strong resistance to abrasion



SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
215/75R17.5	100EV584G	16	H	135/133 J	6.00	6.75	4,805@125	4,540@125	8.3	14.1	30.2	18	688	62
235/75R17.5	100EV642G	16	H	143/141 J (144/144 F)	6.75	7.5	6,005@125	5,675@125	9.2	14.6	31.4	17	662	72
245/70R17.5	100EV870G	16	H	143/141 J (144/144 F)	7.50	6.75	6,005@127	5,675@125	9.8	14.3	31.1	17	668	70

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius