



GT879



Extraordinary All Wheel position Radial designed for Regional Applications



Features

- Five rib tread pattern
- Wide straight grooves
- Cross sipes in intermediate ribs
- Equal rib distribution

Benefits

- ▶ Excellent maneuverability
- ▶ Exceptional water evacuation
- ▶ Enhanced traction and longer tread life
- ▶ Tread scrubbing resistance

SIZE RANGE

TIRE SIZE	PR	LR	LOAD INDEX (s/d)	SS	APPROVED WHEEL	ALLOWED WHEEL	MAX LOAD (s/d)	MAX PRESSURE (s/d)	SECTION WIDTH	SLR	OVERALL DIAMETER	TREAD DEPTH	RPM	WEIGHT
					in	in	lbs	psi	in	in	in	32 nd		lbs
215/75R17.5	16	H	135/133	J	6.00	6.75	4805/4540	125/125	8.5	14.2	30.2	16	682	67
235/75R17.5	14	G	132/130	J	6.75	7.50	4410/4190	110/110	9.3	14.7	31.4	16	668	72
235/75R17.5	16	H	143/141	J	6.75	7.50	6005/5675	125/125	9.3	14.7	31.4	16	668	73
265/70R19.5	16	H	140/138	M	7.50	8.25	5510/5205	115/115	10.4	16.2	34.1	18	612	86
11R22.5	14	G	144/142	M	8.25	7.50	6175/5840	105/105	11.0	19.4	41.5	21	500	127
11R22.5	16	H	148/145	M	8.25	7.50	6940/6395	120/120	11.0	19.4	41.5	21	500	127
295/75R22.5	14	G	144/141	M	9.00	8.25	6175/5675	110/110	11.6	18.7	39.9	21	518	123
12R22.5	16	H	152/148	M	9.00	8.25	7830/6940	123/123	12.0	20.0	42.7	22	486	143
315/80R22.5	18	J	154/151 (156/151)	M	9.00	9.75	8270/7610	120/120	12.4	19.7	42.4	21	493	146
11R24.5	14	G	146/143	M	8.25	7.50	6610/6005	105/105	11.0	20.3	43.5	21	477	136
11R24.5	16	H	149/146	M	8.25	7.50	7160/6610	120/120	11.0	20.3	43.5	21	477	138
285/75R24.5	14	G	144/141	M	8.25	NA	6175/5675	110/110	11.2	19.3	41.3	21	501	123

PR Ply Rating LR Load Range (s/d) Single/Dual SS Speed Symbol SLR Static Loaded Radius



www.gtradialtrucktires.com